


Impact-R 2030/31



Features

- Intel® i5/i7 Processor with Hyperthreading and TurboBoost
- Supports Intel AMT 7.0, RAID 0, 1, 5, 10
- 3 year warranty, first year onsite (UK only)
- Custom colours and OEM branding service available
- Constructed from roadmapped industrial components
- Designed for mission critical 24/7 applications
- Assembled and tested within a lean manufacturing environment under ISO 9001

Dimensions



Impact-R 2030/31

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

Specifications

Hardware specification	Processors incorporated into each model: Impact-R 2030 – Intel® Core™ i5-2400 3.1 GHz, 6M Cache Impact-R 2031 – Intel® Core™ i7-2600 3.4 GHz, 8M Cache Chipset: Intel® Q67 Express Chipset Main memory: 2GB DDR3 1066/1333MHz dual channel (max 32GB*) Video: Integrated Intel® HD Graphics Display Resolution: Resolutions up to 2048 x 1536 @ 75 Hz LAN: 2 ports at 10/100/1000Mbps, support for WOL, PXE Boot ROM, iAMT 7.0 with Intel® 82579LM, 2nd port Intel® 82574L Watchdog Timer: 1-255 sec or 1-255 min TPM: Infineon SLB 9635 TT 1.2 *Usable memory capacity may be limited by the operating system	Environmental storage	Temperature: -20 to 65°C Humidity: 5 to 90% at 25°C non-condensing
	BIOS	AMI	Electromagnetic compatibility (EMC)
Storage	500GB SATA HDD 7200rpm DVD RW (standard height) Total drive capacity: 1 x 5.25" external, 1 x 3.5" external, 3 x 3.5" internal or 1 x Slim 5.25" external, 1 x 3.5" external, 4 x 3.5" internal We can provide storage and backup solutions for any application		
System expansion	1 x PCI 32 Bit PCI slot 250mm length 1 x PCI 32 Bit PCI, 180mm length (to accept half height PCI card with full height bracket) 1 x PCI Express x16 graphics slot Note: - PCI slots are not suitable for high bandwidth cards		Safety
System architecture	Industrial ATX form factor motherboard		
Supported OS (Operating System)	Windows XP, Windows Vista, Windows 7 and Linux. If your desired operating system is not listed or you wish to check support for a specific version of Linux, please contact us.		Electrical Ratings
Internal interfaces	8 connectors for additional external USB 2.0 ports 5 connectors for external COM ports 1 front audio connector 1 CD-in internal audio connector 1 S/PDIF connector 6 Serial ATA ports 1 front panel connector 2 fan connectors		
LEDs and switches	Power (PC ON) LED Hard disk access LED Front: ATX system control switch, system reset		Reliability
External interfaces	1 mini-DIN-6 PS/2 mouse port 1 mini-DIN-6 PS/2 keyboard port 1 VGA port 1 DVI-I port (DVI-D signal only) 2 HDMI 2 RJ45 LAN ports 4 USB ports Mic-in, line-in and line-out jacks		
Mechanical	Design: EIA RS-310C 19" Rackmount Standard Construction: Heavy duty cold rolled electroplated steel Colour: Black (custom colours available for large orders) Dimensions: 483(W) x 88(H) x 450(D) mm (19" x 3.5" x 17.7") Packaging size: 630(W) x 248(H) x 574(D) mm (24.8" x 9.8" x 22.6") Cooling: 3 x 80mm fan, 42.5 CFM each Air filter: removable (washable) Gross weight: approximately 20kg		
Environmental operational	Acoustic noise: 47dBA sound pressure at 23°C (typical) Temperature: 0 to 40°C (tested for extended operation up to 50°C) Humidity: 5 to 90% at 25°C non-condensing Please contact us to discuss extended or harsher environmental specifications Low noise fan options are available (maximum operating temperature 35°C) We can design systems to meet additional requirements		

Model	PCIe slots	PCI slots	Processor
Impact-R 2030	1	2	Intel Core i5-2400
Impact-R 2031	1	2	Intel Core i7-2600